

Stable is everything! SAVR Series

◀ تحت لیسانس ایده آل آلمان

◀ استابلایزر تمام اتوماتیک دیجیتال (تک فاز)

◀ تکنولوژی جدید و متفاوت مجهز به سرو موتور

◀ افزایشدهنده و کاهشدهنده ولتاژ ما بین رنج ۲۶۰ - ۱۴۰ ولت

◀ اصلاح ولتاژ بصورت ولت به ولت

◀ نمایشگر ولتاژ ورودی و خروجی و شدت جریان دیجیتال

◀ مناسب برای تغذیه دقیق کلیه دستگاههای الکترونیکی و کامپیوتری

◀ در رنج و ظرفیتهای متفاوت

نقش پیرداز ایرانیان ایده آل نماینده انحصاری و مرکز پخش در ایران

تهران - سعادت آباد - خیابان علامه طباطبائی - مجتمع تجاری طوس - طبقه اول واحد ۴۰
تلفن : ۸۸۶۹۰۱۸۱ فکس : ۸۸۶۹۰۱۵۳
service@ideal-pie.de




High precision solution Dynamic LCD

SAVR Series/Servo motor type


SAVR-1000VA



SAVR-1500VA



SAVR-2000VA






SAVR-3000VA



SAVR-5000VA

Model	SAVR-1000VA	SAVR-1500VA	SAVR-2000VA	SAVR-3000VA	SAVR-5000VA
Power	1000VA	1500VA	2000VA	3000VA	5000VA
Technology	Digital Circuit + LCD display + Servo Motor				
Input	140 - 260 Vac				
	50/60 Hz				
Output	220 Vac				
	±1%/±3%				
Efficiency	98%				
Phase	Single Phase				
LCD Display Status	Input Voltage/ Output Voltage/ Output Current/ AVR Status				
Protection	High Voltage Protection				
	Yes				
	Low Voltage Protection				
	Yes				
Protection	Overload Protection				
	Yes				
Protection	High Temperature Protection				
	Yes				
Protection	Circuit Protection				
	Circuit Breaker				
Smart Cooling System	N/A				Yes
Safety Standards	CE, EN 60950, EN55024				
Environmental	Operating Temperature				
	0~40°C				
	Storage Temperature				
	-15°C~45°C				
Physical	Operating Relative Humidity				
	10%RH~102%RH; Non-condensing				
	Machine Size (mm)				
	295x150x198	95x150x198	352x220x256	352x220x256	295x150x198
	N.W. (Kgs)	6.9	7.5	8.6	12.35
					13.95


SAVR-1000VA
SAVR-1500VA
SAVR-2000VA




SAVR-3000VA SAVR-5000VA




Three Phase Industry Solution

PDR Series/Servo motor type

Model		PDR-20KVA	PDR-30KVA
Power		20000VA	30000VA
Technology		Digital Circuit + Digital LED display + Servo Motor	
Input	Input Voltage Range	260-430Vac	
	Input Frequency	50/60 Hz	
	Output Voltage	380 Vac	
Output	Output Precision	±3%	
		98%	
Efficiency		Three Phases	
Phase		Input Voltage/ Output Voltage	
LED Display Status	INPUT	Blue; Indicating phase A/B and C input voltage normal/abnormal	
	POWER	Red; Indicating power ON/OFF.	
	DELAY	Yellow; During delay, this LED flashes, delay finished, goes off.	
	OUTPUT	Blue; Indicating the output voltage ON/OFF	
		Yes	
Protection	High Voltage Protection	Yes	
	Low Voltage Protection	Yes	
	Overload Protection	Yes	
	High Temperature Protection	Yes	
Smart Cooling System	Circuit Protection	Circuit Breaker	
		Yes	
Safety Standards		CE, EN 60950, EN55024	
Environmental	Operating Temperature	0~40℃	
	Storage Temperature	-15℃~45℃	
	Operating Relative Humidity	10%RH~102%RH; Non-condensing	
Physical	Machine Size (mm)	735x400x450	785x400x450
	N.W. (Kgs)	75.0	95.0



PDR-20KVA PDR-30KVA



PDR-20KVA



PDR-30KVA

